



GPS Pathfinder Pro XRS receiver

KEY FEATURES

Real-time submeter accuracy

Integrated satellite, beacon, and SBAS differential receiver

EVEREST multipath rejection

Rugged design

Ergonomic, comfortable backpack system

Choice of field computer and field software



HIGH-PERFORMANCE GPS WITH A WORLD OF REAL-TIME OPTIONS

The versatile GPS Pathfinder® Pro XRS receiver is the thoroughbred of GPS receivers. Offering a full range of accurate real-time correction sources, great performance in all GPS conditions, and rugged design for the toughest environments, the Pro XRS receiver is an essential tool for collecting and maintaining GPS data.

Built to meet your demands

With the Pro XRS receiver, you don't have to worry whether you can keep working in harsh conditions. All its components are sealed in a robust casing. Waterproof, dustproof, and shock-resistant, the Pro XRS receiver can work anywhere you can.

Just as tough is the custom-designed ergonomic backpack. But it's light and comfortable, so you can wear it all day.

You're spoiled for real-time choice

If you're navigating in the field, or finding your way back to a previously recorded feature, you've got all the real-time options covered. Corrections from a radiobeacon, the OmniSTAR satellite differential service, or a satellite-based augmentation system (SBAS) like WAAS or EGNOS are not just built in, they're seamlessly integrated into the receiver. Want the freedom to connect to an external correction source like a virtual reference station (VRS)? You've got it. This array of real-time sources makes the Pro XRS receiver the most adaptable real-time GPS receiver around.

High quality, accurate data for your GIS

With the Pro XRS receiver, you can be sure that the data you collect meets your high standards. Offering submeter accuracy real-time, and 50 cm accuracy postprocessed, it's the ideal choice for collecting the high quality GPS data you need in your GIS. And it has advanced design features, like EVEREST™ multipath

rejection technology, to ensure you get only the best positions.

Get the results you want

The GPS Pathfinder Pro XRS receiver's advanced design gives you complete control over GPS quality. You can focus on productivity, to keep working even in adverse GPS conditions. Or you can configure the receiver to deliver only the most precise positions. It's up to you.

Flexible data collection options

Pick the field computer and software that fits your workflow. The Pro XRS receiver is ready to use with a variety of computers, including Trimble's own range of rugged field computers: the Trimble® Recon™ handheld, Trimble Ranger™ handheld, and the GeoExplorer® series.

Choosing software? Trimble's TerraSync™ software or the GPScorrect™ extension for ESRI ArcPad software provides a complete solution from field to office and back. Choose off-the-shelf GPS field software, or use the GPS Pathfinder Tools SDK to build your own application that's totally customized to your needs.

All you need

You need equipment that's as adaptable and hard-working as you are. So when you're choosing GPS equipment, don't compromise. Get a GPS Pathfinder Pro XRS receiver and have it all.

GPS Pathfinder Pro XRS receiver

STANDARD FEATURES

GPS

- Integrated GPS/beacon/satellite/SBAS¹ receiver
- Integrated GPS/beacon/satellite/SBAS antenna
- Real-time differential correction sources:
 - MSK radiobeacon
 - OmniSTAR satellite
 - SBAS¹
- EVEREST multipath rejection technology
- RTCM input/output
- NMEA output

Accessories

- International AC re-charger and power supply
- Rechargeable system batteries (8 hours of field use)
- Ergonomic backpack carrying system
- 3 meter antenna cable

OPTIONAL FEATURES

Software

- TerraSync software
- Trimble GPSCorrect extension for ESRI ArcPad software
- Custom application built using the GPS Pathfinder Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for ESRI ArcGIS software

Field computers

- Field computer running Microsoft® Windows Mobile® 2003 software for Pocket PCs, such as:
 - Trimble Ranger handheld
 - Trimble Recon handheld
 - GeoExplorer series handheld
- Field computer running Microsoft Windows® desktop operating system

Accessories

- Vehicle kit (includes cigarette lighter power adaptor, quick release, 2 quick release adaptors, and magnetic mount)
- Hard carry case

TECHNICAL SPECIFICATIONS

Physical

GPS Receiver

Size 11.1 cm x 5.1 cm x 19.5 cm (4.4 in x 2.0 in x 7.7 in)
Weight 0.76 kg (1.68 lb)

Antenna

Size 15.5 cm diameter x 14 cm high (6.1 in x 5.5 in)
Weight 0.55 kg (1.2 lb)

Power 7 Watts (maximum), 10 to 32 VDC

Environmental

Temperature

Operating -20 °C to +65 °C (-4 °F to +149 °F)
Storage -30 °C to +85 °C (-22 °F to +185 °F)

Humidity 100% fully sealed

Receiver casing Dustproof, splashproof, shock-resistant
Sealed to 5 psi

Antenna casing Dustproof, waterproof, shock-resistant

GPS

Channels 12 (L1 code and carrier)

Integrated real-time SBAS¹

Update rate 1 Hz

Time to first fix 30 seconds (typical)

Protocols TSIP, NMEA (GGA, VTG, GLL, GSA, ZDA, GSV, RMC)

Accuracy (HRMS)² after differential correction

Postprocessed 50 cm

Carrier postprocessed³

With 5 minutes tracking satellites 30 cm

With 10 minutes tracking satellites 20 cm

With 20 minutes tracking satellites 10 cm

With 45 minutes tracking satellites 1 cm

Real-time Submeter

¹ SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only. And EGNOS (European Geostationary Navigation Overlay System) available in Europe only.

² Horizontal Root Mean Squared accuracy. Requires data to be collected with minimum of 4 satellites, maximum PDOP of 6, minimum SNR of 39 dBHz, minimum elevation of 15 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

³ Accuracy varies with proximity to base station by +5 ppm.

Specifications subject to change without notice.

© 1998–2006, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark Office and in other countries. EVEREST, GPS Analyst, GPSCorrect, and TerraSync are trademarks of Trimble Navigation Limited. Ranger and Recon are trademarks of Tripod Data Systems Inc., a wholly owned subsidiary of Trimble Navigation Limited. Microsoft and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. TID13275H (05/06)

NORTH & SOUTH AMERICA

Trimble Navigation Limited
10355 Westmoor Drive
Suite #100
Westminster, CO 80021
USA
+1-720-587-4574 Phone
+1-720-587-4878 Fax

EUROPE, AFRICA & MIDDLE EAST

Trimble GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation
Singapore PTE Limited
80 Marine Parade Road
#22-06 Parkway Parade
Singapore, 449269
SINGAPORE
+65-6348-2212 Phone
+65-6348-2232 Fax

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



www.trimble.com
store.trimble.com